


EASY SET UP GUIDE



1

Connect Ethernet Cable

Unpack **Beacon #1** and plug the Ethernet cable into the blue WAN port on the back of the Beacon.



2

Connect to ONT

Plug the other end of the Ethernet cable into the LAN 1 or GE 1 port on your Optical Network Terminal (ONT). That's the little fibre box attached to your wall.



3

Power on Beacon #1

Connect the power adapter to **Beacon #1** and turn it on. The light should glow White. This Beacon is your main router.



4

Wait for the Blue light

The Beacon's light may flash during set-up, but it will turn solid Blue when ready. **This can take some time so please be patient.** Now's a good time to go grab a cuppa.



5

Power on Beacon #2

When the first Beacon's light turns Blue, unpack **Beacon #2**, find a good location (up to 10 meters away, out in the open and away from other appliances e.g. microwaves) and power it on.



6

Wait for the Blue light

This Beacon's light will also glow White and flash while it connects to Beacon #1. **Again, this can take a few minutes, but please wait for the light to turn solid Blue.**



7

Connect to WiFi

When both Beacons glow Blue, your network is ready to use. Connect your devices using the SSID and WiFi key shown on the base of **Beacon #1** (the one connected to your ONT).



8

Enjoy Powerful WiFi

To learn more about optimising your WiFi, visit: novaenergy.co.nz/powerful-wifi.